




# FIXED CALIPER

**P 32 J**

**20.2007.10**




## DESCRIPTION

Fixed caliper with 2 opposed pistons, realized by semicalipers joined by bolts. Pads are supported by one pin. Construction Material: Aluminium Alloy. Operating fluid: brake fluid DOT3/DOT4.

N.B.: drawing shows left side caliper. Mounting side behind the fork.

## PADS SHAPE AND DIMENSIONS



## TECHNICAL CHARACTERISTICS

Pistons number and diameter:	2 32mm	Average pad surface (1 pad):	10.5 cm <sup>2</sup>
MAX working pressure:	70bar	Weight (with not sintered pads):	0.484 Kg
A) Disc position (TOLERANCE):	±0.4 mm		

## CONFIGURATION

CHARACT. CODE CALIPER	PADS FRICTION MATERIAL	BODY COLOR	MOUNT. SIDE	USABLE DISCS THICKNESS	BRAKE FLUID FOR PADS WEAR
20.2007.10	FER 4402	NATURAL	SX	4.5 mm	6.40 cm <sup>3</sup>

## AVAILABLE SPARE PARTS

SPARE PARTS CODE CALIPER	PADS	BLEEDER SCREW	DUST COVER	PIN, SPRING CLIP
20.2007.10	207.5365.14	205.3246.14	205.1502.11	220.2800.64

Indicating informations subject to modification. For further specifications contact Technical Section.

LAST UPDATE: 19/05/2000