



# FIXED CALIPER

P 32 F

20.5161.86






#### DESCRIPTION

Fixed caliper with 2 opposed pistons, realized by semicalipers joined by bolts. Pads are supported by one pin. Construction Material: Aluminium Alloy. Operating fluid: brake fluid DOT4.

### PADS SHAPE AND DIMENSIONS



### TECHNICAL CHARACTERISTICS

Pistons number and diameter: 2 MAX working pressure: 32 mm 100 bar

Average pad surface (1 pad):

13.3 cm<sup>2</sup>

A) Disc position (TOLERANCE):
Disc thickness 5.0 mm
Disc thickness 4.6/4.0 mm

±0.1 mm ±0.3 mm Weight (with not sintered pad):

0.540 Kg

### CONFIGURATION

CODE CALIPER	PADS FRICTION MATERIAL	BODY COLOR	MOUNT. SIDE	USABLE DISCS THICKNESS	BRAKE FLUID FOR PADS WEAR
20.5161.86	FRENDO 222	NATURAL	SX DX	5.0 mm 4.6 mm 4.0 mm	6.60 cm³

## AVAILABLE SPARE PARTS

CODE PARTS CALIPER	PADS	BLEEDER SCREW	DUST COVER	PIN
20.5161.86	107.2686.41	105.3246.11	105.1502.10	120.2800.11

Indicating informations subject to modification. For further specifications contact Technical Section.

LAST UPDATE: 29/03/1995