



FIXED CALIPER

P 32 G 20.6950.10 D






DESCRIPTION

Fixed caliper with 2 opposed pistons, realized by semicalipers joined by bolts. Pads are supported by one pin. Construction Material: Aluminium Alloy. Operating fluid: brake fluid DOT4.

 $\frac{\text{N.B.:}}{\text{Caliper Code 20.6950.10.}} \label{eq:normalizero} \text{drawing shows caliper Code 20.6950.20 specular.}$

PADS SHAPE AND DIMENSIONS



TECHNICAL CHARACTERISTICS

Pistons number and diameter: 2 32mm
MAX working pressure: 70bar

Average pad surface (1 pad):

16.1 cm²

A) Disc position (TOLERANCE):

±0.5 mm

Weight (with not sintered pads):

0.600 Kg

CONFIGURATION

CODE CALIPER	PADS FRICTION MATERIAL	BODY COLOR	MOUNT. SIDE	USABLE DISCS THICKNESS	BRAKE FLUID FOR PADS WEAR
20.6950.10	FERIT I/D 450 FF	BLACK	SX DX	5.0 mm	6.6 cm³

AVAILABLE SPARE PARTS

CODE PARTS CALIPER	PADS BLEEDER SCREW		DUST COVER	PIN SPLIT SPRING
20.6950.10	107.6949.10	105.3387.10	105.1502.10	120.5116.11

Indicating informations subject to modification. For further specifications contact Technical Section.

LAST UPDATE: 09/02/1999